

WELDPLAST 605

WELDPLAST 605, 230V/3680W,
without shoe, industrial plug
Article 174.422



Article	174.422	
Voltage	230 V	
Frequency	50/60 Hz	
Power	3680 W	
Welding additive	ø 4–5 mm / 0.16–0.2 in	
Material output ø 4 mm	3.9 – 4.8 kg/h	8.59 – 10.58 lb/h
Material output ø 5 mm	4.9 – 6.0 kg/h	10.8 – 13.22 lb/h
Welding materials	HDPE	
	LDPE	
	LLDPE	
Weldable sheet/membrane thickness	1 – 3 mm	0.03 – 0.11 in
Air guide	External	
Screw heating	Coil heater	
Air temperature control	Closed loop	
LQS	Yes	
Display	Yes	
Brushless blower motor	Yes	
Brushless drive motor	Yes	
LED Working light	Yes	
Length	809.0 mm	31.85 in
Width	140.0 mm	5.51 in
Height	273.0 mm	10.74 in
Weight	12.2 kg	26.89 lb
Power cable length	5.0 m	16.4 ft



WELDPLAST 605

WELDPLAST 605, 230V/3680W,
without shoe, industrial plug
Article 174.422

Plug	CEE blue, 3 poles, 16A
Noise emission level	< 70 dB(A)
Approvals	CE
Protection class	I
Country of origin	CH