

WELDPLAST S2 PVC



To the product



Technical data

Voltage	200 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	2400-3000 W	
Welding additive	ø 3-4 mm / 0.12-0.16 in	
Material output ø 3 mm	0.6-1.3 kg/h	1.32-2.86 lb/h
Material output ø 4 mm	1.0-2.0 kg/h	2.2-4.4 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP; PVC-U	
Air guide	External	
Screw heating	Coil heater	
Air temperature control	Closed loop	
LQS	No	
Display	Yes	
Brushless blower motor	Yes	
Brushless drive motor	No	
LED Working light	No	
Length	450.0 mm	17.71 in
Width	98.0 mm	3.85 in
Height	260.0 mm	10.23 in
Weight	5.8 kg	12.78 lb
Power cable length	3.0-5.0 m	9.84-16.4 ft
Noise emission level	78 dB (A)	



WELDPLAST S2 PVC

Technical data

Approvals	CE; KC; UKCA
Protection class	I
Country of origin	CH

Scope of delivery

Welding shoe K8/K10 EA; Tool case

Product items

135.724	WELDPLAST S2 PVC, 230V/3000W, EU plug
140.708	WELDPLAST S2 PVC, 230V/3000W, CN plug
146.342	WELDPLAST S2 PVC, 200V/2400W, w/o plug
156.804	WELDPLAST S2 PVC, 230V/3000W, CEE 3/16
169.929	WELDPLAST S2 PVC, 220V/2750W, KR plug